

DCS 6000 Digital Conference System Conference Units



Channel Selectors



The CS 6032 F is a channel selector unit for fixed mounting either vertical or horizontal as you prefer.

The CS 6032 F is part of the DIS DCS 6000 Digital Conference System. The CS 6032 is connected to the digital communication system bus, which connects directly to the CU 6010/EX 6010 Central Units.

The CS 6032 consist of a PCB with components attached to a painted steel top plate, 3,5mm jack socket, buttons for selection of channels and volume and a 2 characters back illuminated LCD display.

The CS 6032 provides digital sound distribution for up to 32 channels.

The CS 6032 features:

- Digital Sound Transmission.
- Built-in DA-Converter.
- Connection for DIS high quality headphones type DIS DH 900x or DH 800x high impedance.
- Volume control.
- Channel selection ch. 0-31.

How to order

Conference Units:
CS 6032 F

Order no.:
6781

Connection Cable for DCS
6000 components:

EC 6000-0,5	EC 6000-10
EC 6000-01	EC 6000-20
EC 6000-05	EC 6000 -50
0,5 m - 50 m. cables	

DCS 6000 Digital
Conference System
Conference Units

CS 6032 F



Specifications

Comply with relevant international standards such as IEC 914 etc.

Temperature Range:
5-40 deg. Celsius

Headphone connection:
3,5 mm jack female mono/stereo socket
for analogue output.

Weight:
F-type: Approx. 0,10 kg

Connections:
Connector type: 2 x RJ45 8-pin.

Power Requirements:
Supplied from CU 6010/EX 6010.

Frequency response:
20-16 kHz

Power Consumption:
0.6 W (typical)

Dimension (WxHxD mm):
Overall dimensions F-type:
45x95x50

Please refer to the User manual for
specification of numbers of units per
chain.

Data subject to change without notice in interest of
product improvements.